## NSN 5962-01-030-3146

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-030-3146

View Online at https://aerobasegroup.com/nsn/5962-01-030-3146
Body Length:
0.785 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.140 inches and 0.185 inches
Maximum Power Dissipation Rating:
24.4 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Computer control fscm 81205
Features Provided:
Hermetically sealed and low power and monolithic and positive outputs and schottky and w/open collector
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Quad 2 input
Design Function And Quantity:
4 gate, nand
Case Outline Source And Designator:
D-1 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-1.5 volts power source and 5.5 volts power source
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
14 printed circuit
Specification Data:
81349-mil-m-38510/300 government specification
Shelf Life:

--

N/a

**Unit Of Measure:** 

## NSN 5962-01-030-3146

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0