NSN 5962-01-030-3151

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-030-3151

о.	- d		nath:	
nı	mw	1 6		-

Between 1.230 inches and 1.280 inches

Body Width:

Between 0.520 inches and 0.560 inches

Body Height:

Between 0.160 inches and 0.200 inches

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

End Application:

Directional finder set fscm 04071

Features Provided:

Hermetically sealed and monolithic and negative outputs and positive outputs and w/enable and expandable and w/buffered output and wire-or outputs and programmable and programmed and w/decoded output

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

8 input

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-1.5 volts power source and 5.5 volts power source

Time Rating Per Chacteristic:

25.00 nanoseconds propagation delay time, low to high level output and 75.00 nanoseconds propagation delay time, low to high level output

Memory Device Type:

Rom

Memory Capacity:

Unknown

Test Data Document:

04071-r261134 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

24 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Vec - demil/mli

NSN 5962-01-030-3151

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0