NSN 5962-01-030-5280

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-030-5280

View Online at https://aerobasegroup.com/nsn/5962-01-030-5280
Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Maximum Power Dissipation Rating:
600.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
An/fpn-52 mod kit fscm 24930
Features Provided:
Hermetically sealed and monolithic and positive outputs and bipolar
Inclosure Material:
Metal
Inclosure Configuration:
Can
Output Logic Form:
P-type metal oxide-semiconductor logic
Input Circuit Pattern:
6 input
Design Function And Quantity:
1 shift register, dynamic
Case Outline Source And Designator:
T0-99 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-20.0 volts power source and 0.3 volts power source
Time Rating Per Chacteristic:
90.00 nanoseconds propagation delay time, low to high level output
Test Data Document:
24930-g390436 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
8 pin
Shelf Life:
N/a
Unit Of Measure:

Demilitarization: Yes - demil/mli

NSN 5962-01-030-5280

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0