NSN 5962-01-030-6369



Memory Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-030-6369 **Body Length:** Between 0.750 inches and 0.770 inches **Body Width:** Between 0.285 inches and 0.291 inches **Body Height:** Between 0.150 inches and 0.199 inches **Maximum Power Dissipation Rating:** 600.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Processor unit fscm 81205 **Features Provided:** Hermetically sealed and monolithic and asynchronous and synchronous and w/buffered output and expandable and resettable and positive outputs and bipolar **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** P-type metal oxide-semiconductor logic **Input Circuit Pattern:** 8 input **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -20.0 volts power source and 0.3 volts power source **Memory Device Type:** First-in first-out **Memory Capacity:** Unknown **Test Data Document:** 81349-mil-std-883 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 16 printed circuit

Demilitarization:

Unit Of Measure:

Shelf Life:

N/a

NSN 5962-01-030-6369

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0