NSN 5962-01-030-7986

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-030-7986
Body Length:
Between 0.745 inches and 0.755 inches
Body Width:
Between 0.245 inches and 0.252 inches
Body Height:
Between 0.115 inches and 0.125 inches
Maximum Power Dissipation Rating:
60.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Digital data set type an/fsq-111 fscm 81995
Features Provided:
Monolithic and positive outputs and adjustable
Inclosure Material:
Plastic
Plastic Inclosure Configuration:
Inclosure Configuration:
Inclosure Configuration: Dual-in-line
Inclosure Configuration: Dual-in-line Input Circuit Pattern:
Inclosure Configuration: Dual-in-line Input Circuit Pattern: 3 input
Inclosure Configuration: Dual-in-line Input Circuit Pattern: 3 input Design Function And Quantity:
Inclosure Configuration: Dual-in-line Input Circuit Pattern: 3 input Design Function And Quantity: 1 amplifier, video and 1 amplifier, wideband Terminal Surface Treatment: Tin
Inclosure Configuration: Dual-in-line Input Circuit Pattern: 3 input Design Function And Quantity: 1 amplifier, video and 1 amplifier, wideband Terminal Surface Treatment: Tin Time Rating Per Chacteristic:
Inclosure Configuration: Dual-in-line Input Circuit Pattern: 3 input Design Function And Quantity: 1 amplifier, video and 1 amplifier, wideband Terminal Surface Treatment: Tin Time Rating Per Chacteristic: 15.00 nanoseconds propagation delay time, low to high level output
Inclosure Configuration: Dual-in-line Input Circuit Pattern: 3 input Design Function And Quantity: 1 amplifier, video and 1 amplifier, wideband Terminal Surface Treatment: Tin Time Rating Per Chacteristic: 15.00 nanoseconds propagation delay time, low to high level output Shelf Life:
Inclosure Configuration: Dual-in-line Input Circuit Pattern: 3 input Design Function And Quantity: 1 amplifier, video and 1 amplifier, wideband Terminal Surface Treatment: Tin Time Rating Per Chacteristic: 15.00 nanoseconds propagation delay time, low to high level output Shelf Life: N/a
Inclosure Configuration: Dual-in-line Input Circuit Pattern: 3 input Design Function And Quantity: 1 amplifier, video and 1 amplifier, wideband Terminal Surface Treatment: Tin Time Rating Per Chacteristic: 15.00 nanoseconds propagation delay time, low to high level output Shelf Life:
Inclosure Configuration: Dual-in-line Input Circuit Pattern: 3 input Design Function And Quantity: 1 amplifier, video and 1 amplifier, wideband Terminal Surface Treatment: Tin Time Rating Per Chacteristic: 15.00 nanoseconds propagation delay time, low to high level output Shelf Life: N/a Unit Of Measure:
Inclosure Configuration: Dual-in-line Input Circuit Pattern: 3 input Design Function And Quantity: 1 amplifier, video and 1 amplifier, wideband Terminal Surface Treatment: Tin Time Rating Per Chacteristic: 15.00 nanoseconds propagation delay time, low to high level output Shelf Life: N/a

Fiig: A458a0