

View Online at <https://aerobasegroup.com/nsn/5962-01-031-1136>

Body Outside Diameter:

Between 0.590 inches and 0.610 inches

Body Height:

Between 0.140 inches and 0.180 inches

Maximum Power Dissipation Rating:

2.25 watts

Operating Temperature Range:

+0.0/+80.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Nato seasparrow sms fscm 49956

Features Provided:

Hermetically sealed and hybrid and w/strobe and positive outputs and negative outputs

Inclosure Material:

Glass and metal

Inclosure Configuration:

Can

Input Circuit Pattern:

2 input

Design Function And Quantity:

1 driver, line

Case Outline Source And Designator:

T0-8 joint electron device engineering council

Terminal Surface Treatment:

Tin

Time Rating Per Characteristic:

6.00 nanoseconds propagation delay time, low to high level output

Test Data Document:

10001-2891659 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A458a0