NSN 5962-01-031-7029

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-031-7029

Body Length:
0.390 inches
Body Width:
Between 0.235 inches and 0.280 inches
Body Height:
Between 0.045 inches and 0.085 inches
Maximum Power Dissipation Rating:
303.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Antenna type as-1920/msc-46 fscm 15942
Features Provided:
Hermetically sealed and monolithic and positive outputs
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Quad 2 input
Case Outline Source And Designator:
F-2 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-1.5 volts power source and 5.5 volts power source
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
14 flat leads
Specification Data:
81349-mil-m-38510-153 government specification
Shelf Life:
N/a
Unit Of Measure:

Yes - demil/mli

Demilitarization:

NSN 5962-01-031-7029

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0