NSN 5962-01-031-7923

Digital Microcircuit - Page 1 of 1

Fiig: A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-031-7923

Body Length:
1.290 inches
Body Width:
Between 0.500 inches and 0.610 inches
Body Height:
Between 0.150 inches and 0.210 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and high performance and positive outputs
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
6 input
Design Function And Quantity:
1 decoder, four to sixteen line
Case Outline Source And Designator:
D-3 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-1.5 volts power source and 5.5 volts power source
Time Rating Per Chacteristic:
36.00 nanoseconds propagation delay time, low to high level output and 33.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
10001-2509556 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
24 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli