

View Online at <https://aerobasegroup.com/nsn/5962-01-032-2011>

Body Length:

Between 0.745 inches and 0.755 inches

Body Width:

Between 0.245 inches and 0.252 inches

Body Height:

Between 0.115 inches and 0.125 inches

Maximum Power Dissipation Rating:

600.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Receiver fscm 50464

Features Provided:

Monolithic and resettable and retriggerable and adjustable and positive outputs and high current

Inclosure Material:

Plastic

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

Dual 4 input

Design Function And Quantity:

2 timer

Terminal Surface Treatment:

Tin

Time Rating Per Characteristic:

100.00 nanoseconds propagation delay time, low to high level output

Test Data Document:

81349-mil-std-883 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0