# NSN 5962-01-032-2013

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-032-2013

## **Body Length:**

Between 1.850 inches and 2.150 inches

## Body Width:

Between 1.850 inches and 2.150 inches

## **Body Height:**

Between 0.380 inches and 0.400 inches

## **Operating Tempurature Range:**

-0.0/+70.0 degrees celsius

## Storage Tempurature Range:

-25.0/+85.0 degrees celsius

## **End Application:**

Circuit card assembly p/n 73-509649-1 fscm 11530

## **Features Provided:**

Hermetically sealed and hybrid and negative outputs and positive outputs and adjustable

### Inclosure Material:

Metal

## Inclosure Configuration:

Dual-in-line

## Input Circuit Pattern:

16 input

## **Design Function And Quantity:**

1 converter, digital to analog

# **Terminal Surface Treatment:**

Gold

## Voltage Rating And Type Per Characteristic:

-15.45 volts power source and 15.45 volts power source

## Time Rating Per Chacteristic:

10000.00 nanoseconds propagation delay time, low to high level output

## **Precious Material And Location:**

Terminals gold

#### **Precious Material:**

Gold

# Test Data Document:

04655-15-509660 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## Terminal Type And Quantity:

32 printed circuit

#### Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

# NSN 5962-01-032-2013

Linear Microcircuit - Page 2 of 2

**Fiig:** A458a0

