

View Online at <https://aerobasegroup.com/nsn/5962-01-032-2022>

**Body Length:**

Between 0.770 inches and 0.870 inches

**Body Width:**

Between 0.220 inches and 0.280 inches

**Body Height:**

Between 0.145 inches and 0.185 inches

**Maximum Power Dissipation Rating:**

500.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Circuit card assembly fscm 06481

**Features Provided:**

Hermetically sealed and monolithic and adjustable and negative outputs and positive outputs and w/strobe

**Inclosure Material:**

Glass and metal

**Inclosure Configuration:**

Dual-in-line

**Input Circuit Pattern:**

Dual 4 input

**Design Function And Quantity:**

2 comparator, voltage, differential

**Terminal Surface Treatment:**

Gold

**Voltage Rating And Type Per Characteristic:**

15.0 volts power source

**Time Rating Per Characteristic:**

500.00 nanoseconds propagation delay time, low to high level output and 500.00 nanoseconds propagation delay time, high to low level output

**Precious Material And Location:**

Terminals gold and body gold

**Precious Material:**

Gold

**Test Data Document:**

06481-971095 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

16 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0