NSN 5962-01-032-2024

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-032-2024

Body Length:	
0.840 inches	
Body Width:	
Between 0.220 inches	and 0.310 inches
Body Height:	
Between 0.140 inches	and 0.185 inches
Maximum Power Dis	sipation Rating:
1200.0 milliwatts	
Operating Tempurat	ire Range:
-55.0/+125.0 degrees	celsius
Storage Tempuratur	e Range:
-65.0/+150.0 degrees	celsius
End Application:	
Circuit card assembly	p/n 791250 and p/n 791290
Features Provided:	
Hermetically sealed a	nd monolithic and negative outputs and positive outputs
Inclosure Material:	
Ceramic and glass	
Inclosure Configurat	ion:
Dual-in-line	
Input Circuit Pattern	
4 channel	
Design Function And	Quantity:
2 switch, analog	
Case Outline Source	And Designator:
D-2 mil-m-38510	
Terminal Surface Tre	atment:
Tin	
Voltage Rating And ⁻	Type Per Characteristic:
15.0 volts power sour	ce
Time Rating Per Cha	cteristic:
1000.00 nanoseconds	propagation delay time, low to high level output and 1000.00 nanoseconds propagation delay time, high to low level
output	
Test Data Document	
06481-971082 drawin	g (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specifica	tion, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And G	luantity:
16 printed circuit	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
Yes - demil/mli	

NSN 5962-01-032-2024

Linear Microcircuit - Page 2 of 2

Fiig: A458a0

