## NSN 5962-01-032-2028

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-032-2028
Body Length:
0.280 inches
Body Width:
Between 0.240 inches and 0.280 inches
Body Height:
Between 0.030 inches and 0.085 inches
Maximum Power Dissipation Rating:
170.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Dcsr segment fscm 14155
Features Provided:
Hermetically sealed and monolithic and complementary outputs and retriggerable and w/clear and positive outputs
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
5 input
Design Function And Quantity:
1 multivibrator, monostable
Case Outline Source And Designator:
F-1 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
14 flat leads
Specification Data:
81349-mil-m-38510/12 government specification
Shelf Life:
N/a

-

**Unit Of Measure:** 

## NSN 5962-01-032-2028

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0