

View Online at <https://aerobasegroup.com/nsn/5962-01-032-2030>

Body Length:

Between 0.371 inches and 0.409 inches

Body Width:

Between 0.247 inches and 0.283 inches

Body Height:

Between 0.060 inches and 0.075 inches

Maximum Power Dissipation Rating:

150.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Emc pod fscm 94990

Features Provided:

Hermetically sealed and monolithic and high speed and w/enable and positive outputs

Inclosure Material:

Glass and metal

Inclosure Configuration:

Flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

Dual 3 input

Design Function And Quantity:

2 decoder, one of four line

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

5.5 volts power source

Time Rating Per Characteristic:

30.00 nanoseconds propagation delay time, low to high level output

Precious Material And Location:

Terminals gold

Test Data Document:

81349-mil-std-883 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0