

View Online at <https://aerobasegroup.com/nsn/5962-01-032-6845>

**Body Length:**

Between 0.371 inches and 0.409 inches

**Body Width:**

Between 0.247 inches and 0.283 inches

**Body Height:**

Between 0.050 inches and 0.075 inches

**Maximum Power Dissipation Rating:**

50.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Navigation-display set type an/asn-124 fscm 35351

**Features Provided:**

Hermetically sealed and monolithic and positive outputs and low power and dual edge triggered and complementary outputs and w/clear and resettable and negative edge triggered

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Flat pack

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

Dual 3 input

**Design Function And Quantity:**

2 multivibrator, monostable

**Time Rating Per Characteristic:**

75.00 nanoseconds propagation delay time, low to high level output

**Precious Material And Location:**

Terminals gold

**Test Data Document:**

81349-mil-std-883 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0