

View Online at <https://aerobasegroup.com/nsn/5962-01-032-6846>

Body Length:

Between 0.371 inches and 0.409 inches

Body Width:

Between 0.247 inches and 0.283 inches

Body Height:

Between 0.050 inches and 0.075 inches

Maximum Power Dissipation Rating:

45.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Navigation-display set type an/asn-124 fscm 35351

Features Provided:

Hermetically sealed and monolithic and positive outputs and w/enable and complementary outputs and low power and w/buffered output

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

12 input

Design Function And Quantity:

1 multiplexer

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 5.5 volts power source

Time Rating Per Characteristic:

80.00 nanoseconds propagation delay time, low to high level output

Test Data Document:

35351-153416 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

16 flat leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0