# NSN 5962-01-032-6855

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-032-6855

# **Body Length:**

Between 0.371 inches and 0.409 inches

# **Body Width:**

Between 0.247 inches and 0.283 inches

# **Body Height:**

Between 0.050 inches and 0.075 inches

# **Maximum Power Dissipation Rating:**

75.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### End Application:

Navigation-display set type an/asn-124 fscm 35351

#### **Features Provided:**

Hermetically sealed and monolithic and positive outputs and low power and synchronous and high speed and w/enable and resettable

#### **Inclosure Material:**

Ceramic and glass

# Inclosure Configuration:

Flat pack

# **Output Logic Form:**

Transistor-transistor logic

#### Input Circuit Pattern:

9 input

## **Design Function And Quantity:**

1 shift register, parallel and/or series operation

## **Terminal Surface Treatment:**

Solder

## Voltage Rating And Type Per Characteristic:

5.5 volts power source

## Test Data Document:

35351-154795 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# Terminal Type And Quantity:

16 flat leads

## Shelf Life:

N/a

# Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

#### Fiig:

A458a0