## NSN 5962-01-033-0757

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-033-0757

Body Length:
Between 0.660 inches and 0.800 inches
Body Width:
Between 0.220 inches and 0.291 inches
Body Height:
Between 0.179 inches and 0.199 inches
Maximum Power Dissipation Rating:
100.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Counter measure fscm 94117
Features Provided:
Hermetically sealed and monolithic and positive outputs and edge triggered and resettable and complementary outputs and w/clear
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Dual 3 input
Design Function And Quantity:
2 multivibrator, monostable
Time Rating Per Chacteristic:
35.00 nanoseconds propagation delay time, low to high level output
Test Data Document:
94117-310263 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A458a0