NSN 5962-01-033-0757

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-033-0757

| Body Length: |
|--|
| Between 0.660 inches and 0.800 inches |
| Body Width: |
| Between 0.220 inches and 0.291 inches |
| Body Height: |
| Between 0.179 inches and 0.199 inches |
| Maximum Power Dissipation Rating: |
| 100.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| Counter measure fscm 94117 |
| Features Provided: |
| Hermetically sealed and monolithic and positive outputs and edge triggered and resettable and complementary outputs and w/clear |
| Inclosure Material: |
| Ceramic and glass |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| Dual 3 input |
| Design Function And Quantity: |
| 2 multivibrator, monostable |
| Time Rating Per Chacteristic: |
| 35.00 nanoseconds propagation delay time, low to high level output |
| Test Data Document: |
| 94117-310263 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A458a0 |