NSN 5962-01-033-2232

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-033-2232 **Body Length:** 0.730 inches **Body Width:** 0.280 inches **Body Height:** Between 0.120 inches and 0.150 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Cnt mes set an/tlq-17a fscm 72314 **Features Provided:** Hermetically sealed and monolithic and positive outputs and w/buffered output **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Quad 2 input **Design Function And Quantity:** 4 comparator, voltage **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** -0.3 volts power source and 15.3 volts power source **Test Data Document:** 81349-mil-std-883 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 14 printed circuit Shelf Life: N/a **Unit Of Measure:**

Demilitarization: Yes - demil/mli

Fiig:

A458a0