NSN 5962-01-033-2236

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-033-2236

Bodv	l er	nath:
Dogv		IMUI.

Between 0.240 inches and 0.260 inches

Body Width:

Between 0.240 inches and 0.260 inches

Body Height:

Between 0.050 inches and 0.065 inches

Maximum Power Dissipation Rating:

160.0 milliwatts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

End Application:

Navigation-display set type an/asn-124 fscm 35351

Features Provided:

Hermetically sealed and monolithic and positive outputs and high speed and expandable and w/open collector

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

Dual 4 input

Design Function And Quantity:

2 expander, and-or

Case Outline Source And Designator:

T0-86 joint electron device engineering council

Terminal Surface Treatment:

Gold

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 5.5 volts power source

Precious Material And Location:

Terminals gold

Test Data Document:

35351-154951 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

14 flat leads

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5962-01-033-2236

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0