# NSN 5962-01-033-2255

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-033-2255

# **Body Length:**

Between 0.747 inches and 0.815 inches

# Body Width:

Between 0.220 inches and 0.280 inches

# **Body Height:**

0.200 inches

**Maximum Power Dissipation Rating:** 

525.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+200.0 degrees celsius

#### **End Application:**

Building block 57 fscm 30003

#### **Features Provided:**

Hermetically sealed and monolithic and positive outputs and w/enable and programmable and programmed and high speed and wire-or outputs

#### Inclosure Material:

Ceramic and glass

#### Inclosure Configuration:

Dual-in-line

#### **Output Logic Form:**

Transistor-transistor logic

#### **Input Circuit Pattern:**

10 input

#### **Time Rating Per Chacteristic:**

60.00 nanoseconds propagation delay time, low to high level output

#### **Precious Material And Location:**

Terminals gold

# Test Data Document:

06424-10560 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

Yes - demil/mli

Fiig:

A458a0