## NSN 5962-01-033-2258

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-033-2258

Body Length	:
-------------	---

Between 0.240 inches and 0.260 inches

**Body Width:** 

Between 0.240 inches and 0.260 inches

**Body Height:** 

Between 0.050 inches and 0.065 inches

**Maximum Power Dissipation Rating:** 

35.0 milliwatts

### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### **Storage Tempurature Range:**

-65.0/+150.0 degrees celsius

#### **End Application:**

Navigation-display set type an/asn-124 fscm 35351

#### **Features Provided:**

Hermetically sealed and monolithic and positive outputs and high speed

#### **Inclosure Material:**

Ceramic and glass

## **Inclosure Configuration:**

Flat pack

## **Output Logic Form:**

Transistor-transistor logic

#### **Input Circuit Pattern:**

8 input

## **Design Function And Quantity:**

1 gate, nand

## **Case Outline Source And Designator:**

T0-86 joint electron device engineering council

#### **Terminal Surface Treatment:**

Gold

## Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 5.5 volts power source

## **Precious Material And Location:**

Terminals gold

#### **Test Data Document:**

35351-154952 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## **Terminal Type And Quantity:**

14 flat leads

## Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5962-01-033-2258

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0