NSN 5962-01-033-2264

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-033-2264

View Online at https://aerobasegroup.com/nsn/5962-01-033-2264
Body Length:
Between 0.371 inches and 0.409 inches
Body Width:
Between 0.247 inches and 0.283 inches
Body Height:
Between 0.050 inches and 0.075 inches
Maximum Power Dissipation Rating:
30.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Navigation-display set type an/asn-124 fscm 35351
Features Provided:
Hermetically sealed and monolithic and positive outputs and low power and asynchronous and w/clear
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Dual 5 input
Design Function And Quantity:
2 flip-flop, j-k, clocked
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 5.5 volts power source
Precious Material And Location:
Terminals gold
Test Data Document:
35351-153424 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
16 flat leads
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

Yes - demil/mli

NSN 5962-01-033-2264

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0