## NSN 5962-01-033-4120

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-033-4120
Body Length:
Between 0.745 inches and 0.770 inches
Body Width:
Between 0.240 inches and 0.260 inches
Body Height:
Between 0.055 inches and 0.140 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and buffered reset and w/buffered output and monolithic
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
2 input and 7 stage
Design Function And Quantity:
1 counter, binary
Case Outline Source And Designator:
Mo-001ad joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
15.0 volts power source
Time Rating Per Chacteristic:
700.00 nanoseconds propagation delay time, low to high level output and 700.00 nanoseconds propagation delay time, high to low level
output
Terminal Type And Quantity:
14 printed circuit
Specification Data:
07690-453270-02 manufacturers source control
Shelf Life:
N/a

Demilitarization:

**Unit Of Measure:** 

Yes - demil/mli

## NSN 5962-01-033-4120

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0