

View Online at <https://aerobasegroup.com/nsn/5962-01-033-7761>

**Body Length:**

0.280 inches

**Body Width:**

Between 0.240 inches and 0.260 inches

**Body Height:**

Between 0.030 inches and 0.085 inches

**Maximum Power Dissipation Rating:**

11.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Receiver type r-1444/urr fscm 80058

**Features Provided:**

Hermetically sealed and monolithic and positive outputs and low power and presettable and w/clear

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Flat pack

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

9 input

**Design Function And Quantity:**

1 flip-flop, j-k, and input master slave

**Case Outline Source And Designator:**

F-1 mil-m-38510

**Voltage Rating And Type Per Characteristic:**

6.0 volts power source

**Time Rating Per Characteristic:**

10.00 nanoseconds propagation delay time, low to high level output and 125.00 nanoseconds propagation delay time, low to high level output

**Precious Material And Location:**

Terminals gold

**Test Data Document:**

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

14 flat leads

**Specification Data:**

81349-mil-m-38510/21 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0