

View Online at <https://aerobasegroup.com/nsn/5962-01-034-2143>

**Body Length:**

Between 1.260 inches and 1.280 inches

**Body Width:**

Between 0.760 inches and 0.780 inches

**Body Height:**

Between 0.190 inches and 0.210 inches

**Maximum Power Dissipation Rating:**

2.5 watts

**Operating Temperature Range:**

-55.0/+110.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

An/asn-124 fscm 35351

**Features Provided:**

Hermetically sealed and multichip and hybrid and adjustable and negative outputs and positive outputs

**Inclosure Material:**

Glass and metal

**Inclosure Configuration:**

Dual-in-line

**Input Circuit Pattern:**

10 input

**Design Function And Quantity:**

1 regulator, voltage

**Terminal Surface Treatment:**

Gold

**Voltage Rating And Type Per Characteristic:**

15.0 volts power source

**Time Rating Per Characteristic:**

30.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, low to high level output

**Precious Material And Location:**

Terminals gold and body gold

**Test Data Document:**

16224-985124 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

24 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0