## NSN 5962-01-034-2143

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-034-2143
Body Length:
Between 1.260 inches and 1.280 inches
Body Width:
Between 0.760 inches and 0.780 inches
Body Height:
Between 0.190 inches and 0.210 inches
Maximum Power Dissipation Rating:
2.5 watts
Operating Tempurature Range:
-55.0/+110.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
An/asn-124 fscm 35351
Features Provided:
Hermetically sealed and multichip and hybrid and adjustable and negative outputs and positive outputs
Inclosure Material:
Glass and metal
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
10 input
Design Function And Quantity:
1 regulator, voltage
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
15.0 volts power source
Time Rating Per Chacteristic:
30.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, low to high level
output
Precious Material And Location:
Terminals gold and body gold
Test Data Document:
16224-985124 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
24 printed circuit
Shelf Life:
N/a

**Demilitarization:** Yes - demil/mli

**Unit Of Measure:** 

## NSN 5962-01-034-2143

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0