

View Online at <https://aerobasegroup.com/nsn/5962-01-034-2144>

**Body Length:**

Between 1.395 inches and 1.405 inches

**Body Width:**

Between 0.530 inches and 0.540 inches

**Body Height:**

0.115 inches

**Maximum Power Dissipation Rating:**

1200.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

An/asn-124 fscm 35351

**Features Provided:**

Hermetically sealed and negative outputs and positive outputs and w/enable and w/buffered output and w/decoded output

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Input Circuit Pattern:**

16 channel

**Design Function And Quantity:**

1 multiplexer, analog

**Terminal Surface Treatment:**

Gold

**Voltage Rating And Type Per Characteristic:**

15.0 volts power source

**Time Rating Per Characteristic:**

300.00 nanoseconds propagation delay time, low to high level output

**Precious Material And Location:**

Terminal surfaces gold

**Precious Material:**

Gold

**Test Data Document:**

35351-157000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

28 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0