

View Online at <https://aerobasegroup.com/nsn/5962-01-034-2144>

Body Length:

Between 1.395 inches and 1.405 inches

Body Width:

Between 0.530 inches and 0.540 inches

Body Height:

0.115 inches

Maximum Power Dissipation Rating:

1200.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

An/asn-124 fscm 35351

Features Provided:

Hermetically sealed and negative outputs and positive outputs and w/enable and w/buffered output and w/decoded output

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

16 channel

Design Function And Quantity:

1 multiplexer, analog

Terminal Surface Treatment:

Gold

Voltage Rating And Type Per Characteristic:

15.0 volts power source

Time Rating Per Characteristic:

300.00 nanoseconds propagation delay time, low to high level output

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Test Data Document:

35351-157000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

28 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0