NSN 5962-01-034-2145

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-034-2145
Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
Between 0.140 inches and 0.185 inches
Maximum Power Dissipation Rating:
670.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
5840-01-020-5631
Features Provided:
Hermetically sealed and monolithic and negative outputs and positive outputs and externally compensated
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
4 input
Design Function And Quantity:
1 amplifier, operational, general purpose
Case Outline Source And Designator:
T0-116 joint electron device engineering council
Terminal Surface Treatment:
Gold or tin
Voltage Rating And Type Per Characteristic:
10.0 volts power source
Precious Material And Location:
Terminals gold
Test Data Document:
21908-186-1023 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:

Demilitarization: Yes - demil/mli

NSN 5962-01-034-2145

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0