

View Online at <https://aerobasegroup.com/nsn/5962-01-034-9827>

Body Length:

Between 1.190 inches and 1.230 inches

Body Width:

Between 0.580 inches and 0.610 inches

Body Height:

Between 0.080 inches and 0.120 inches

Maximum Power Dissipation Rating:

805.0 milliwatts

Operating Temperature Range:

+0.0/+75.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Multiplexer fscm 52483

Features Provided:

Hermetically sealed and monolithic and high speed and schottky and w/enable and w/disable and w/strobe and w/register output and programmable and programmed and 3-state output and w/buffered output and w/decoded output

Inclosure Material:

Ceramic and metal

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

12 input

Time Rating Per Characteristic:

40.00 nanoseconds propagation delay time, low to high level output and 35.00 nanoseconds propagation delay time, high to low level output

Precious Material And Location:

Terminals gold

Precious Material:

Gold

Test Data Document:

52483-104225 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0