# NSN 5962-01-035-5413

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-035-5413

Body I	Length:
--------	---------

Between 0.660 inches and 0.785 inches

**Body Width:** 

Between 0.220 inches and 0.280 inches

**Body Height:** 

Between 0.140 inches and 0.180 inches

**Maximum Power Dissipation Rating:** 

335.0 milliwatts

### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### **Storage Tempurature Range:**

-65.0/+150.0 degrees celsius

#### **End Application:**

Radar set type an/fps-108 fscm 49956

#### **Features Provided:**

Hermetically sealed and monolithic and positive outputs and schottky and high speed and complementary outputs

# **Inclosure Material:**

Ceramic and glass

# **Inclosure Configuration:**

Dual-in-line

# **Output Logic Form:**

Transistor-transistor logic

#### **Input Circuit Pattern:**

9 input

# **Design Function And Quantity:**

1 generator, parity, checker

# **Case Outline Source And Designator:**

T0-116 joint electron device engineering council

#### **Terminal Surface Treatment:**

Solder

# Voltage Rating And Type Per Characteristic:

5.5 volts power source

#### **Test Data Document:**

81349-mil-std-883 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Terminal Type And Quantity:**

14 printed circuit

# Shelf Life:

N/a

#### **Unit Of Measure:**

--

#### **Demilitarization:**

Yes - demil/mli

# NSN 5962-01-035-5413

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0