

View Online at <https://aerobasegroup.com/nsn/5962-01-035-5801>

**Body Length:**

0.280 inches

**Body Width:**

Between 0.240 inches and 0.260 inches

**Body Height:**

Between 0.030 inches and 0.085 inches

**Maximum Power Dissipation Rating:**

268.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Adc program test set fscm 97384

**Features Provided:**

Hermetically sealed and monolithic and positive outputs and high speed and w/totem pole output

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Flat pack

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

Dual 4 input

**Design Function And Quantity:**

2 gate, nand buffer

**Case Outline Source And Designator:**

F-1 mil-m-38510

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-1.5 volts power source and 5.5 volts power source

**Time Rating Per Characteristic:**

2.00 nanoseconds propagation delay time, low to high level output and 20.00 nanoseconds propagation delay time, low to high level output

**Test Data Document:**

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

14 flat leads

**Specification Data:**

81349-mil-m-38510/24 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0