NSN 5962-01-035-7219

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-035-7219

View Online at https://aerobasegroup.com/nsn/5962-01-035-7219
Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Aircraft model e3a fscm 81205
Features Provided:
Hermetically sealed and monolithic and medium power and positive outputs
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Output Logic Form:
Resistor-transistor logic
Input Circuit Pattern:
Dual 2 input
Design Function And Quantity:
2 gate, nand-nor
Case Outline Source And Designator:
T0-99 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-4.0 volts power source and 4.0 volts power source
Time Rating Per Chacteristic:
12.00 nanoseconds propagation delay time, low to high level output
Test Data Document:
49671-1711158 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
8 pin
Shelf Life:
N/a
Unit Of Measure:

Yes - demil/mli

Demilitarization:

NSN 5962-01-035-7219

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0