

View Online at <https://aerobasegroup.com/nsn/5962-01-035-7477>

**Body Length:**

Between 0.755 inches and 0.785 inches

**Body Width:**

Between 0.265 inches and 0.291 inches

**Body Height:**

Between 0.150 inches and 0.199 inches

**Maximum Power Dissipation Rating:**

410.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Common age type f-tf-15 fscm 99999

**Features Provided:**

Hermetically sealed and monolithic and high speed and synchronous and schottky and presettable and w/enable and resettable and positive outputs

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

9 input

**Design Function And Quantity:**

1 counter, binary

**Time Rating Per Characteristic:**

9.00 nanoseconds propagation delay time, low to high level output

**Test Data Document:**

81349-mil-std-883 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0