NSN 5962-01-035-7477



Digital Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-01-035-7477 **Body Length:** Between 0.755 inches and 0.785 inches **Body Width:** Between 0.265 inches and 0.291 inches **Body Height:** Between 0.150 inches and 0.199 inches **Maximum Power Dissipation Rating:** 410.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Common age type f-tf-15 fscm 99999 **Features Provided:** Hermetically sealed and monolithic and high speed and synchronous and schottky and presettable and w/enable and resettable and positive outputs **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 9 input **Design Function And Quantity:** 1 counter, binary **Time Rating Per Chacteristic:** 9.00 nanoseconds propagation delay time, low to high level output **Test Data Document:** 81349-mil-std-883 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0