

View Online at <https://aerobasegroup.com/nsn/5962-01-035-9197>

Body Length:

0.896 inches

Body Width:

Between 0.220 inches and 0.310 inches

Body Height:

Between 0.140 inches and 0.185 inches

Maximum Power Dissipation Rating:

625.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Signal data converter @p/n 220-27121-101 fscm 80378

Features Provided:

Hermetically sealed and bipolar and monolithic and positive outputs and programmable and programmed and schottky and 3-state output and w/enable

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

6 input

Case Outline Source And Designator:

D-2 mil-m-38510

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-1.0 volts power source and 5.5 volts power source

Time Rating Per Characteristic:

60.00 nanoseconds propagation delay time, low to high level output

Memory Device Type:

Rom

Memory Capacity:

Unknown

Test Data Document:

96214-802986 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0