NSN 5962-01-037-4480

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-037-4480

Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
Between 0.140 inches and 0.180 inches
Maximum Power Dissipation Rating:
750.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
A-10a weapon system fscm 77751
Features Provided:
Hermetically sealed and monolithic and negative outputs and positive outputs and w/enable and w/field effect transistor switch
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
2 channel
Design Function And Quantity:
1 driver, switch, field effect transistor
Case Outline Source And Designator:
T0-116 joint electron device engineering council
Terminal Surface Treatment:
Tin
Time Rating Per Chacteristic:
1000.00 nanoseconds propagation delay time, low to high level output
Test Data Document:
81349-mil-std-883 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Fiig:

A458a0

Yes - demil/mli