# NSN 5962-01-037-4480

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-037-4480

## **Body Length:**

Between 0.660 inches and 0.785 inches

## **Body Width:**

Between 0.220 inches and 0.280 inches

# **Body Height:**

Between 0.140 inches and 0.180 inches

## **Maximum Power Dissipation Rating:**

750.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### End Application:

A-10a weapon system fscm 77751

#### **Features Provided:**

Hermetically sealed and monolithic and negative outputs and positive outputs and w/enable and w/field effect transistor switch

#### **Inclosure Material:**

Ceramic and glass

# Inclosure Configuration:

Dual-in-line

#### Input Circuit Pattern:

2 channel

#### Design Function And Quantity:

1 driver, switch, field effect transistor

#### Case Outline Source And Designator:

T0-116 joint electron device engineering council

#### **Terminal Surface Treatment:**

Tin

#### Time Rating Per Chacteristic:

1000.00 nanoseconds propagation delay time, low to high level output

#### **Test Data Document:**

81349-mil-std-883 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

Yes - demil/mli

#### Fiig:

A458a0