## NSN 5962-01-037-4501

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-037-4501

view Offinie at https://defobasegroup.com/nsn/3302-01-037-4301
Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
Between 0.140 inches and 0.180 inches
Maximum Power Dissipation Rating:
165.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Countermeasures set type an/tlq-17a
Features Provided:
Hermetically sealed and monolithic and positive outputs
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Emitter-coupled logic
Input Circuit Pattern:
11 input
Design Function And Quantity:
1 detector, phase
Case Outline Source And Designator:
T0-116 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.0 volts power source
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:
<del></del>

Demilitarization:

Yes - demil/mli

## **NSN 5962-01-037-4501**Digital Microcircuit - Page 2 of 2



Fiig:

A458a0