NSN 5962-01-037-4503



Memory Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-037-4503 **Body Length:** 0.870 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** Between 0.140 inches and 0.180 inches **Maximum Power Dissipation Rating:** 332.8 milliwatts **Operating Tempurature Range:** +0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Receiver, radio type r-2045/grr-3 (v) **Features Provided:** Monolithic and high speed and programmable and w/buffered output and w/enable and expandable and w/open collector and positive outputs and programmed and w/decoded output and w/disable **Inclosure Material:** Plastic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 6 input **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** -1.5 volts power source and 5.5 volts power source **Time Rating Per Chacteristic:** 50.00 nanoseconds propagation delay time, low to high level output **Memory Device Type:** Rom **Memory Capacity:** Unknown **Test Data Document:** 05828-4827-0141 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:**

--

N/a

16 printed circuit

Unit Of Measure:

Shelf Life:

NSN 5962-01-037-4503

Memory Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0