# NSN 5962-01-037-4506

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-037-4506

# **Body Length:**

0.870 inches

# **Body Width:**

Between 0.240 inches and 0.260 inches

# **Body Height:**

Between 0.140 inches and 0.180 inches

# **Operating Tempurature Range:**

+0.0/+70.0 degrees celsius

## Storage Tempurature Range:

-65.0/+150.0 degrees celsius

## **Features Provided:**

Monolithic and programmable and programmed and schottky and w/enable and positive outputs and 3-state output

## Inclosure Material:

Plastic

## Inclosure Configuration:

Dual-in-line

# **Output Logic Form:**

Transistor-transistor logic

## Input Circuit Pattern:

10 input

**Terminal Surface Treatment:** 

Solder

# Voltage Rating And Type Per Characteristic:

-1.2 volts power source and 5.5 volts power source

# **Time Rating Per Chacteristic:**

75.00 nanoseconds propagation delay time, low to high level output

#### Memory Device Type:

Rom

#### Memory Capacity:

Unknown

# Test Data Document:

20227-10366000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# Terminal Type And Quantity:

16 printed circuit

#### Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

Yes - demil/mli

#### Fiig:

A458a0