NSN 5962-01-037-4509

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-037-4509

| Body Length: | |
|---|--------------|
| 0.280 inches | |
| Body Width: | |
| Between 0.240 inches and 0.260 inches | |
| Body Height: | |
| Between 0.030 inches and 0.085 inches | |
| Maximum Power Dissipation Rating: | |
| 138.0 milliwatts | |
| Operating Tempurature Range: | |
| -55.0/+125.0 degrees celsius | |
| Storage Tempurature Range: | |
| -65.0/+150.0 degrees celsius | |
| End Application: | |
| Navigation-display set type an/asn-124 fscm 35351 | |
| Features Provided: | |
| Hermetically sealed and monolithic and positive outputs and complementary outputs and retriggerable and edge triggered | |
| Inclosure Material: | |
| Ceramic and glass | |
| Inclosure Configuration: | |
| Flat pack | |
| Output Logic Form: | |
| Transistor-transistor logic | |
| Input Circuit Pattern: | |
| 4 input | |
| Design Function And Quantity: | |
| 1 multivibrator, monostable | |
| Case Outline Source And Designator: | |
| F-1 mil-m-38510 | |
| Terminal Surface Treatment: | |
| Solder | |
| Voltage Rating And Type Per Characteristic: | |
| -1.5 volts power source and 5.5 volts power source | |
| Test Data Document: | |
| 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in sp | pecification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on ce | rtain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | |
| Terminal Type And Quantity: | |
| 14 flat leads | |
| Specification Data: | |
| 94240 mil m 29540/42 sourcement experiment | |

81349-mil-m-38510/12 government specification

Shelf Life:

N/a

- Unit Of Measure:
- --

NSN 5962-01-037-4509

Digital Microcircuit - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

