## NSN 5962-01-037-4511

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-037-4511

**Body Length:** 

0.896 inches

**Body Width:** 

Between 0.220 inches and 0.310 inches

**Body Height:** 

Between 0.140 inches and 0.185 inches

**Maximum Power Dissipation Rating:** 

200.0 milliwatts

**Operating Tempurature Range:** 

-55.0/+125.0 degrees celsius

**Storage Tempurature Range:** 

-65.0/+175.0 degrees celsius

**End Application:** 

Navigation-display set type an/asn-124 fscm 35351

**Features Provided:** 

Hermetically sealed and monolithic and positive outputs and asynchronous and edge triggered and medium speed and synchronous and w/buffered output

**Inclosure Material:** 

Ceramic and glass

**Inclosure Configuration:** 

Dual-in-line

**Output Logic Form:** 

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:** 

8 stage

**Design Function And Quantity:** 

1 shift register, parallel and/or series operation and 1 shift register, static

**Case Outline Source And Designator:** 

D-2 mil-m-38510

**Terminal Surface Treatment:** 

Solder

**Voltage Rating And Type Per Characteristic:** 

15.0 volts power source

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

16 printed circuit

**Specification Data:** 

81349-mil-m-38510/57 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5962-01-037-4511

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0