NSN 5962-01-037-4523

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-037-4523 **Body Length:** Between 1.200 inches and 1.300 inches **Body Width:** Between 0.550 inches and 0.650 inches **Body Height:** Between 0.170 inches and 0.200 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** +0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Test panel type uor-1ls fscm 27914 **Features Provided:** Hermetically sealed and monolithic and positive outputs and w/enable and 3-state output and programmable and programmed and w/buffered output **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** N-type metal oxide-semiconductor logic **Input Circuit Pattern:** 13 input **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 5.5 volts power source **Memory Device Type:** Rom **Memory Capacity:** Unknown **Test Data Document:** 27914-51035 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 24 printed circuit Shelf Life: N/a

Yes - demil/mli

Unit Of Measure:

Demilitarization:

NSN 5962-01-037-4523

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0