NSN 5962-01-037-4536

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-037-4536
Overall Length:
0.326 inches
Body Length:
0.280 inches
Body Width:
Between 0.240 inches and 0.260 inches
Body Height:
Between 0.030 inches and 0.085 inches
Maximum Power Dissipation Rating:
36.6 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Navigation-display set type an/asn-124 fscm 35351
Features Provided:
Hermetically sealed and monolithic and positive outputs and low power and schottky and w/totem pole output and electrostatic sensitive
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Hex 1 input
Criticality Code Justification:
Cbbl
Design Function And Quantity:
6 inverter, digital
Case Outline Source And Designator:
F-1 mil-m-38510
Terminal Surface Treatment:
Solder
Product Name:
Hex, 1-input inverter gate
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 7.0 volts power source and -1.5 volts input and 5.5 volts input
Time Rating Per Chacteristic:

Test Data Document:

output

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

2.00 nanoseconds propagation delay time, low to high level output and 20.00 nanoseconds propagation delay time, low to high level

NSN 5962-01-037-4536

Digital Microcircuit - Page 2 of 2



Terminal	Type	And	Quantity:
----------	------	-----	-----------

14 flat leads

Specification Data:

81349-mil-m-38510/300 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0