NSN 5962-01-037-6372

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-037-6372

Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Maximum Power Dissipation Rating:
85.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Classification set, sonar type an/bqq-3b
Features Provided:
Hermetically sealed and monolithic and high gain and low power and negative outputs and positive outputs and internally compensated
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Input Circuit Pattern:
Dual 2 input
Case Outline Source And Designator:
T0-100 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
15.0 volts power source
Time Rating Per Chacteristic:
300.00 nanoseconds propagation delay time, low to high level output
Test Data Document:
02387-72h02n178 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
10 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig:

A458a0