NSN 5962-01-037-6373

Linear Microcircuit - Page 1 of 1



view Online at https://aerobasegroup.com/nsn/5962-01-037-6373
Body Length:
Between 0.340 inches and 0.390 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
Between 0.130 inches and 0.180 inches
Maximum Power Dissipation Rating:
800.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs and high voltage and medium speed
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
Dual 2 input
Design Function And Quantity:
2 driver, peripheral
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
65.00 nanoseconds propagation delay time, low to high level output
Test Data Document:
81349-mil-std-883 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
8 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig:

A458a0