NSN 5962-01-037-6781

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-037-6781
Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
Between 0.140 inches and 0.180 inches
Maximum Power Dissipation Rating:
80.0 milliwatts
Operating Tempurature Range:
+0.0/+85.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Recorder-reproducer group, signal data type oa-8609a/sqq-3
Features Provided:
Hermetically sealed and monolithic and positive outputs and w/buffered output
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
8 input
Design Function And Quantity:
2 gate, nand buffer
Case Outline Source And Designator:
T0-116 joint electron device engineering council
Time Rating Per Chacteristic:
48.00 nanoseconds propagation delay time, low to high level output and 48.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
56232-1603009 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig:

A458a0